

# 2MP Fixed Dual-light Turret Network Camera

IPC-T132-AF28-DL-ECO



2 MP



Dual-light



Built-in Mic



Human body  
detection 2.0



HLC

Ultra  
H.265



PoE



IP67

## Features

- High quality image with 2MP, 1/3" CMOS sensor
- 2MP(1920\*1080)@30fps;720P (1280\*720)@30fps
- Ultra 265, H.265, H.264
- 2D/3D DNR (Digital Noise Reduction)
- ROI (Region of Interest)
- Smart IR, up to 30m (98ft) IR distance
- 3 Axis
- Built in Mic
- Wide temperature range: -30 °C to 60 °C ( -22 °F to 140 °F)
- Support PoE power supply
- IP67

## Specifications


|                |                      |
|----------------|----------------------|
| Model          | IPC-T132-AF28-DL-ECO |
| Camera         |                      |
| Max Resolution | 2 MP                 |
| Sensor         | 1/3.0" CMOS          |

|                                    |                                                                                                                                                             |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Min. Illumination                  | Colour: 0.005Lux (F1.6, AGC ON)<br>0 Lux with IR on                                                                                                         |
| Day/Night                          | IR-cut filter with auto switch (ICR)                                                                                                                        |
| Shutter                            | Auto/Manual, 1 to 1/100000 s                                                                                                                                |
| Adjustment Angle                   | Pan: 0° ~ 360°, Tilt: 0° ~ 80°, Rotate: 0° ~ 360°                                                                                                           |
| S/N                                | > 52 dB                                                                                                                                                     |
| WDR                                | DWDR                                                                                                                                                        |
| Lens                               |                                                                                                                                                             |
| Focal Length                       | 2.8 mm                                                                                                                                                      |
| Iris                               | F1.6                                                                                                                                                        |
| Field of View (H)                  | 85.1°                                                                                                                                                       |
| Field of View (V)                  | 46.6°                                                                                                                                                       |
| Field of View (D)                  | 95.5°                                                                                                                                                       |
| DORI                               |                                                                                                                                                             |
| DORI Distance (Lens)               | 2.8 mm                                                                                                                                                      |
| DORI Distance (Detect)             | 51.4m(168.7ft)                                                                                                                                              |
| DORI Distance (Observe)            | 20.6m(67.5ft)                                                                                                                                               |
| DORI Distance (Recognize)          | 10.3m(33.7ft)                                                                                                                                               |
| DORI Distance (Identify)           | 5.1m(16.9ft)                                                                                                                                                |
| Illuminator                        |                                                                                                                                                             |
| Supplemental Light                 | Dual light                                                                                                                                                  |
| Illumination Distance (IR)         | 30 m (98.4 ft)                                                                                                                                              |
| Illumination Distance (Warm Light) | 15 m (49.3 ft)                                                                                                                                              |
| Wavelength                         | 850 nm                                                                                                                                                      |
| IR On/Off Control                  | Auto/Manual                                                                                                                                                 |
| Video                              |                                                                                                                                                             |
| Video Compression                  | Ultra 265, H.265, H.264                                                                                                                                     |
| H.264 Code Profile                 | Baseline profile, Main profile, High profile                                                                                                                |
| Frame Rate                         | Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps;<br>Sub Stream: 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; |
| Video Bit Rate                     | 128 Kbps to 6144 Kbps                                                                                                                                       |
| U-code                             | Support                                                                                                                                                     |
| OSD                                | Up to 4 OSDs                                                                                                                                                |
| Privacy Mask                       | Up to 4 areas                                                                                                                                               |
| ROI                                | Up to 8 areas                                                                                                                                               |
| Video Stream                       | Dual streams                                                                                                                                                |
| Image                              |                                                                                                                                                             |
| White Balance                      | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2, Area white balance                                                                                    |
| Digital Noise Reduction            | 2D/3D DNR                                                                                                                                                   |
| Smart IR                           | Support                                                                                                                                                     |
| Flip                               | Normal, Flip vertical, Flip horizontal, 180°                                                                                                                |
| Dewarping                          | N/A                                                                                                                                                         |
| HLC                                | Support                                                                                                                                                     |

|                        |                                                                                                                               |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| BLC                    | Support                                                                                                                       |
| Defog                  | Digital defog                                                                                                                 |
| <b>Events</b>          |                                                                                                                               |
| Basic Detection        | Motion detection, Audio detection, Human body detection 2.0                                                                   |
| General Function       | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication |
| <b>Audio</b>           |                                                                                                                               |
| Audio Compression      | G.711U, G.711A                                                                                                                |
| Audio Bitrate          | 64 Kbps                                                                                                                       |
| Two-way Audio          | N/A                                                                                                                           |
| Suppression            | Support                                                                                                                       |
| Sampling Rate          | 8 kHz                                                                                                                         |
| <b>Network</b>         |                                                                                                                               |
| Protocols              | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, DNS, DDNS, NTP, UPnP, HTTP, QoS, RTCP, RTMP                                 |
| Compatible Integration | ONVIF (Profile S, Profile T) ,<br>API, SDK                                                                                    |
| User/Host              | Up to 32 users. 2 user levels: administrator and common user                                                                  |
| Client                 | Uniarch client, Uniarch app                                                                                                   |
| Web Browser            | Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+                                                                     |
| <b>Interface</b>       |                                                                                                                               |
| Audio I/O              | N/A                                                                                                                           |
| Alarm I/O              | N/A                                                                                                                           |
| Built-in Mic           | Support                                                                                                                       |
| Built-in Speaker       | N/A                                                                                                                           |
| WIFI                   | N/A                                                                                                                           |
| Network                | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                                                          |
| Video Output           | N/A                                                                                                                           |
| <b>Certification</b>   |                                                                                                                               |
| EMC                    | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035)<br>FCC (FCC 47 CFR part15 B)                                      |
| Safety                 | CE LVD (EN 62368-1)                                                                                                           |
| Environment            | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);                                                                         |
| Protection             | IP67 (IEC 60529)                                                                                                              |
| <b>General</b>         |                                                                                                                               |
| Power                  | PoE (IEEE 802.3af)<br>Power consumption: Max 3.5W                                                                             |
| Power Interface        | N/A                                                                                                                           |
| Dimensions             | Φ118 x 100mm (Ø4.6" x 3.9")                                                                                                   |
| Weight                 | 0.19kg (0.42lb)                                                                                                               |
| Material               | Graphene + Plastic                                                                                                            |
| Working Environment    | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                       |
| Storage Environment    | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                       |

|                     |                     |
|---------------------|---------------------|
| Surge Protection    | 4 KV                |
| Reset Button        | N/A                 |
| Web Client Language | 1 Language: English |

## Dimensions



## Accessories

### TR-JB03-I-IN

Junction Box for Plastic Turret Camera(Support wiring from behind)



### TR-JB07/WM03-G-IN

Wall Mounting Assembling Bracket For 32 Fix-dome&Mini Fix-dome&Plastic Turret Camera



### TR-WM03-D-IN

Wall Mounting Bracket for 32 Fix-dome&Mini Fix-dome&Plastic Turret Camera



TR-A01-IN

NPT 3/4" Waterproof Cable Gland



TR-UP06-IN

Universal Pole Mounting Bracket



TR-UC08-C

Bullet&Dome Corner Mounting Bracket



TR-WM07P-B

Dome Wall Mounting Plastic Bracket



TR-SM05-IN

Switch Box Adapter for Fixed Dome



TR-CM24-IN

Dome Pendant Mounting Bracket(Indoor)



TR-SE24-IN

Dome Pendant Mounting Pole 200mm



TR-SE24-A-IN

Dome Pendant Mounting Pole 500mm



**Zhejiang Uniview Technologies Co., Ltd.**

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.